

Ladder Cable Tray - Weights, kg/m

Tray Width (mm)	Rung Spacing (mm)	ELL3	EHL4	ETL4	ELL6	ETL6	EHZ6	EHL6	D-EHL6	EHL8	D-EHL10
150	150	3.1	4.6	4.6	6.8	4.4	7.3	6.8	7.5	9.6	14.2
	235	2.8	4.3	4.3	6.5	4.1	6.9	6.5	7.2	9.3	13.9
	300	2.6	4.1	4.1	6.3	3.9	6.8	6.3	7.0	9.1	13.7
	470	2.5	4.0	4.0	6.1	3.7	6.6	6.1	6.8	9.0	13.5
225	150	3.5	5.0	5.0	7.2	4.8	7.6	7.2	7.9	10.0	14.6
	235	3.0	4.5	4.5	6.7	4.3	7.2	6.7	7.4	9.5	14.1
	300	2.8	4.3	4.3	6.5	4.1	7.0	6.5	7.2	9.3	13.9
	470	2.6	4.1	4.1	6.2	3.9	6.7	6.2	6.9	9.1	13.6
300	150	3.8	5.3	5.3	7.5	5.1	8.0	7.5	8.2	10.3	14.9
	235	3.2	4.7	4.7	6.9	4.5	7.4	6.9	7.6	9.7	14.3
	300	3.0	4.5	4.5	6.7	4.3	7.1	6.7	7.3	9.5	14.1
	470	2.7	4.2	4.2	6.4	4.0	6.8	6.4	7.0	9.2	13.8
450	150	4.5	6.0	6.0	8.2	5.8	8.7	8.2	8.9	11.0	15.6
	235	3.7	5.2	5.2	7.4	5.0	7.8	7.4	8.1	10.2	14.8
	300	3.3	4.8	4.8	7.0	4.6	7.5	7.0	7.7	9.8	14.4
	470	2.9	4.4	4.4	6.6	4.2	7.1	6.6	7.3	9.4	14.0
600	150	5.2	6.7	6.7	8.9	6.5	9.4	8.9	9.6	11.7	16.3
	235	4.2	5.6	5.6	7.8	5.4	8.3	7.8	8.5	10.6	15.2
	300	3.7	5.2	5.2	7.4	5.0	7.8	7.4	8.0	10.2	-
	470	3.1	4.6	4.6	6.8	4.4	7.3	6.8	7.5	9.6	-
750	150	5.9	7.4	7.4	9.6	7.2	10.1	9.6	10.3	12.4	-
	235	4.6	6.1	6.1	8.3	5.9	8.8	8.3	9.0	11.1	-
	300	4.0	5.5	5.5	7.7	5.3	8.2	7.7	8.4	10.5	-
900	150	6.6	8.1	8.1	10.3	7.9	10.8	10.3	11.0	13.1	-
	235	5.1	6.6	6.6	8.7	6.3	9.2	8.7	9.4	11.6	-
	300	4.4	5.9	5.9	8.1	5.7	8.5	8.1	8.7	10.9	-

Values are applicable to all resin systems, where possible.